

ISDN 8510T

Point to Point ☐ or Multipoint ☐ XJM: (Y or N) ☐
(if Multipoint, list shared users) _____

AMI ☐ or 2B1Q ☐ * Key System ☐

Circuit ID _____ IBZD _____ ..CV

* Order # _____ CONFIG _____

Call Pickup Group _____

Call Forward Busy to _____

Call Forward Don't Answer to _____ # of Rings ☐

Does Primary # appear on other sets? (Y or N) ☐

INTERCOM: Intercom Group _____

Dial ☐ or Auto ☐ * Intercom Code # _____

JACKS: RJ11C ☐ or RJ45X ☐ New ☐ or Existing ☐

VOICE MAIL: (Y or N) ☐ Optml: (Y or N) ☐ BTI: (Y or N) ☐

Revert to Operator Number _____ Mailbox Size _____

Pager Type & Number or PIN _____

BULK POWER (if known): (Y or N) ☐

REMARKS Speed Call 30 Individual.

NOTES: On call appearances please indicate Ring, No Ring, or Delay or Abbreviated Ring (if Delay or Abbreviated Ring show number of rings).
Show special requirements in REMARKS section, i.e.: Packet Switched Data, Circuit Switched Data, Additional Intercoms, Call Pickup Groups, etc.
Bell Atlantic will complete * items.

CUSTOMER'S NAME _____

PRIMARY NUMBER _____ FLR/RM _____

INDIVIDUAL USER'S NAME _____

OGTS number _____ Agency number _____

ISDN 8510T

1	6
2	7
3	8
4	9
5	10

▼

▲

Message ☐

☐ Mute

Redial

1

2

DEF 3

☐ Speaker

Exit

4

JKL 5

MNO 6

☐ Conf

Drop

PQRS 7

TUV 8

9

☐ Transfer

Hold

*

OPER 0

#